

°STELPRO

HIGH-END FAN HEATER

FOR BATHROOMS – ASORB SERIES

CUSTOMIZED COMFORT!

The °STELPRO family of high-end ORLÉANS™ convectors is growing. Treat yourself to our brand new ORLÉANS™ high-end fan heater and enjoy a toasty warm bathroom even in the wintertime. Thanks to its optimum heat output and rapid rise in temperature, this model provides heat exactly when you need it. It is also the quietest fan heater in its category, allowing you to relax and enjoy peace and quiet. Very similar to our ORLÉANS™ high-end convector, it features an optional built-in thermostat that's smart home ready.

IDEAL FOR:

BATHROOMS, ENTRANCES, VESTIBULES, HALLWAYS,
LIVING SPACES

THE QUIETEST FAN HEATER IN ITS CATEGORY

"HEAT BOOST" MODE

FAST TEMPERATURE INCREASE (1000 W TO 2000 W) †

STURDY, DURABLE AND RUST-RESISTANT

OPTIONAL BUILT-IN THERMOSTAT

PERFECT FOR THE SMART HOME

MODELS WITH THERMOSTAT



PERFECT FOR THE SMART HOME THANKS
TO ITS BUILT-IN MAESTRO SMART
THERMOSTAT



MAESTRO™
ORCHESTRATING COMFORT

zigbee
FEATURES THE ZIGBEE PROTOCOL

PART OF THE ORLÉANS™
FAMILY OF PRODUCTS



ORLÉANS™



COLORS

- standard: white, soft white
- ORORA (optional): denim blue, midnight blue, turquoise, moss green, canary yellow, red, orange, anodized aluminum paint, gravel gray, charcoal, espresso, black (refer to page 8 of the catalogue)

FINISH

epoxy-polyester powdercoat

MANUFACTURING

- high performance polymer cabinet, 20-gauge satin-finish steel front with moulded aluminum edges
- centrifugal fan ensuring a quiet and efficient airflow
- thermal protection with automatic reset
- additional thermal protection with a thermal fuse (must be replaced after shutdown)
- top front air intake and bottom front air discharge

ELEMENT

high-quality nichrome element producing instant heat

CONTROL

MODEL WITH BUILT-IN THERMOSTAT:

- built-in MAESTRO™ smart thermostat featuring the Zigbee protocol
- smart optimum heat output :
 - programmable desired maximum temperature, built-in timer (0-10-20-30-60 min.), rapid forced-air heat (2000 W)
 - automatic heat boost (2000 W) if there's a temperature difference of 7 °F or more between the ambient and setpoint temperature
- power consumption indicator switches from green to red based on the setpoint temperature requested

– open window sensor

MODEL WITHOUT THERMOSTAT:

- an electronic wall thermostat is recommended

INSTALLATION

- recessed or surface mounted (surface adapter: optional)
- on the wall with a minimum of 6 in. from the floor
- easy installation of the front with only one mounting screw
- choice of 2000 W or 1000 W with a power switch upon installation (model without thermostat only).

°STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. Returns are not accepted for orders of products with optional colours. For all the latest models and updated prices, please refer to our web site at www.stelpro.com. * Three years on electronic components.

† 5°C (9°F) temperature rise within 5 minutes. (Tests performed with the 2000 W model in a 70 ft² room).



TECHNICAL SPECIFICATIONS

PRODUCT	THERMOSTAT HEATING	TIMER HEATING	WITHOUT THERMOSTAT	VOLTAGE	HEIGHT	LENGTH	WEIGHT
CODE	WATTS	WATTS	WATTS	VOLTS	IN.	IN.	LB
ASORB1501WC	---	---	1500	120	15 11/16	12 11/16	9.4
ASORB2002M	1000/750	2000/1500	---	240/208	15 11/16	12 11/16	9.4
ASORB2002WC	---	---	2000/1500 or 1000/750*	240/208	15 11/16	12 11/16	9.4

Add W for white or SW for soft white (consult the optional color chart and contact your °STELPRO representative for all other colors).
 * Selected when installed with a power switch

TECHNICAL DRAWINGS

